

481 Medium Green Cellulose Acetate

Sheeting – P/P

Product Description

Available gauge range of 0.015" to 0.060" with polished surfaces. This material is designed to meet the requirements of ANSI Z87.1.

Technical Properties

Property	Test Method	Value 0.015 – 0.030"	Value 0.031 – 0.060"
Tensile Strength	ASTM D-882	5,000 psi	4,500 psi
Tensile Elongation	ASTM D-882	25% Minimum	25% Minimum
Water Absorption (24 hrs @ 23°C)	ASTM D-570	9.0% Maximum	7.5% Maximum
Light Transmission	ASTM D-1003	19-27%	19-27%
Flammability	ASTM D-568	0.05 In ² /sec	1.0 In ² /sec
Flammability	ASTM D-635	-	3.0 In/Min Maximum

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**