

Extreme Plus D

High Performance Laminated Thermoplastic Polyolefin

Product Description

Extreme Plus D is a high-melt-strength thermoplastic polyolefin (TPO) sheet engineered for improved thermoforming characteristics and has a laminated film layer. This laminated film layer can impart numerous aesthetic improvements. It can be a decorative printed film. It can serve as a tie layer for bonding or painting. It will improve the scratch mar performance.

Technical Properties

Property	Test Method	Value*
Specific Gravity	ASTM D-792	1.10
Tensile Strength	ASTM D-638	2,800 psi
Tensile Modulus	ASTM D-638	350,000 psi
Flexural Modulus	ASTM D-790	320,000 psi
Mold Shrinkage	Internal	0.007"-0.009"
Izod Impact (Notched) 73°F	ASTM D-256	13.0 ft-lbs./in
Heat Deflection Temperature (@66 psi)	ASTM D-648	238°F
Coefficient of Linear Thermal Expansion	ASTM D-696	2.4x10 ⁻⁵ in/in/°C
Gardner Gloss (60°)	ASTM D-523	20%
Flammability	FMVSS 302	0.060"

**All values based on 0.125"
unless otherwise stated*

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**