

Floorlite G

Flexible TPO Sheet

Product Description

Floorlite G is a lightweight, durable, flexible, low density sheet solution designed for automotive flooring applications.

Technical Properties

Property	Test Method	Value*
Specific Gravity (color dependent)	ASTM D-792	0.88
Flexural Modulus	ISO 178	90 MPa
Tensile Strength - Die A	ASTM D-412	1625 psi
Tensile Elongation at Break	ASTM D-412	1140%
Tear Strength - Die C	ASTM D-624	290 psi
Hardness - Shore A	ASTM D-2240	81
Hardness - Shore D	ASTM D-2240	30
Vicat Softening Temperature	ASTM D-1525	60°C
Cold Flex	-30 °C/0.250" mandrel	Passes

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**