

Formalloy

High Performance Polyolefin

Product Description

Formalloy is a high-melt-strength thermoplastic polyolefin (TPO) sheet engineered for improved thermoforming characteristics. Formalloy can deliver a high or low-gloss surface finish with the tremendous strength and durability of a TPO substrate.

Technical Properties

Property	Test Method	Value*
Specific Gravity	ASTM D-792	1.14
Tensile Strength	ASTM D-638	3,300 psi
Flexural Modulus	ASTM D-790	300,000 psi
Mold Shrinkage	Internal	0.80%
Izod Impact (Notched) 73°F	ASTM D-256	6.5 ft-lbs/in
Heat Deflection Temperature (@66 psi)	ASTM D-648	225°F
Coefficient of Linear Thermal Expansion	ASTM D-696	2.8×10^{-5} in/in/°C
Gardner Gloss (High Gloss, Smooth Sheet)	ASTM D-523	80-85 Gloss Units-60°
Flammability	UL 94-HB	Passes at 0.060"
Flammability	FMVSS 302	Passes at 0.060"

**All values based on 0.125" unless otherwise stated*

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**