

HMWPE

High-Molecular-Weight High-Density Polyethylene

Product Description

HMWPE is a high-molecular-weight, high-density polyethylene sheet with outstanding physical performance. It has high impact strength and rigidity. HMWPE has outstanding chemical resistance. Its low temperature strength and processability further characterize this highly versatile sheet product.

Technical Properties

Property	Test Method	Value*
Specific Gravity (color dependent)	ASTM D-792	0.95
Tensile Strength	ASTM D-638	3,800 psi
Tensile Elongation at Break	ASTM D-638	>600 %
Flexural Modulus	ASTM D-790	170,000 psi
Hardness - Shore D	ASTM D-2240	67
Heat Deflection Temperature (@66 psi)	ASTM D-648	160°F
Coefficient of Linear Thermal Expansion	ASTM D-696	7.0 x10-5 in/in/°F
Flammability	MVSS302	Passes
		<i>*All values based on 0.125" unless otherwise stated</i>

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**