

Korad® 55000- Acrylic Film

Product Description

Korad™ High Gloss Black opaque custom colored film with weatherable pigments. An opaque capping film used to protect and extend the life of extruded sheet in interior and exterior applications. Korad™ film is easily embossed and deep-draw thermoformed for custom applications. Provides excellent color uniformity and retention throughout the life of the product..

- Excellent Thermoforming characteristics and bond strength to multiple substrates
- Printable
- Provides enhanced chemical resistance
- Industry leading UV and weathering resistance

Substrates: ABS; HIPS; PC; PVC; ASA; PMMA.

Korad™ is available as a custom film roll stock product with roll widths up to 110" and in gauges 0.003" to 0.006".

Technical Properties

Property	Test Method	Value
Specific Gravity (color dependent)	ASTM D-792	1.14
Area Yield		56.2 ft ² /lb
Gloss (60°)	ASTM D-523	67 %
Luminous Transmission	ASTM D-1003	<1 %
UV Transmission (280-380 nm)	ASTM D-1003	<1 %
Tensile Strength	ASTM D-882	3,800 psi
Tensile Elongation	ASTM D-882	140 %

**typical values at .003"*

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**