

PC/ABS

Polycarbonate ABS sheet

Product Description

Spartech's PC/ABS is a high-performance Polycarbonate ABS sheet product which exhibits a reduced coefficient of linear thermal expansion. Thermoforming engineers looking for a product with enhanced dimensional stability as well as an excellent balance of physical and mechanical properties, this PC/ABS represents a great alternative to painted metal or fiberglass.

Technical Properties

Property	Test Method	Value
Specific Gravity	ASTM D-792	1.22
Tensile Modulus	ASTM D-638	440,000 psi
Tensile Strength	ASTM D-638	8,500 psi
Izod Impact (Notched) 72°F	ASTM D-256	8.0 ft-lbs/in
Izod Impact (Notched) -22°F	ASTM D-256	1.6 ft-lbs/in
Heat Deflection Temperature (@ 264 psi)	ASTM D-648	248 °F
Flexural Strength	ASTM D-790	13,000
Flexural Modulus	ASTM D-790	430,000
Rockwell Hardness (R Scale)	ASTM D-785	115
Flammability	MVSS 302	Passes @ 0.060"
Coefficient of Linear Thermal Expansion	ASTM D-696	3.7×10^{-5} in/in/°F

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**