

# Rejuven8Plus™

## Forming Grade Proprietary Bio-Based Blend

### Product Description

Rejuven8Plus™ is an environmentally friendly plastics solution that is over 90% Bio-based and mineral-based. It is a plastic sheet derived from plants that are an annually renewable resource. Rejuven8Plus™ sheet is engineered for use in most thermoforming applications. It is a white opaque material that has similar strength properties to APET and PVC, and is PVC-free.

### Technical Properties

Property	Test Method	Value
Specific Gravity	ASTM D-792	1.25
Melt Flow Rate	ASTM D-1238	13.5 g/10 min
Tensile Elongation at Break	ASTM D-638	72%
Tensile Strength	ASTM D-638	7,990 psi
Flexural Strength	ASTM D-790	12,800 psi
Flexural Modulus	ASTM D-790	526,000 psi
Gardner Drop	ASTM D-5420	105 in-lb.

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail [info@spartech.com](mailto:info@spartech.com) or visit our website at [www.spartech.com](http://www.spartech.com)

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**