

Royalite® G50

Fire-Rated sheet

Product Description

Royalite® G50 is a flame rated sheet product. This product is an excellent material for wall coverings, ceiling tiles and a myriad of other architectural applications where stringent building codes are required. Royalite G50 is engineered to pass the ASTM E84 Steiner Tunnel test.

Technical Properties

Property	Test Method	Value*
Specific Gravity (color dependent)	ASTM D-792	1.27
Izod Impact (Notched) 72°F	ASTM D-256	1.5 ft-lbs/in
Tensile Strength	ASTM D-638	7,000 psi
Flexural Strength	ASTM D-790	10,500 psi
Flexural Modulus	ASTM D-790	320,000 psi
Rockwell Hardness (R Scale)	ASTM D-785	95
Heat Deflection Temperature (@ 264 psi - annealed)	ASTM D-648	160°F
Resistance of Synthetic Polymeric Materials to Fungi	ASTM G-21	Passes
Flammability ⁽¹⁾	ASTM E84	Passes <25 flame spread <450 smoke developed

**All values based on 0.125" unless otherwise stated*

¹ Gauge: upto 0.080" unbonded and upto 0.125 when bonded to ¼" cement board. Tested as manufactured, Spartech recommends testing as final construction before installation.

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**