

Royalite® R105

PVC/Acrylic

Product Description

Royalite® R105 is a soft, vinyl foam laminated FR PVC/Acrylic sheet. Royalite® R105 is designed for aircraft cabin, cockpit, and seat components. The sheet has excellent physical characteristics such as impact strength and ductility. Royalite® R105 passes FAR 25.853 (a)(i) @ 0.125" and FAR 25.853 (a)(ii) @ 0.125".

Technical Properties

Property	Test Method	Value*
Specific Gravity (color dependent)	ASTM D-792	1.04
Tensile Strength	ASTM D-638	4,000 psi
Flexural Modulus	ASTM D-790	77,100 psi
Heat Deflection Temperature (@264 psi)	ASTM D-648	69°C
Hardness – Shore D	ASTM D-2240	73
Izod Impact (Notched) 72°F	ASTM D-256	12.2 ft-lb/inch
Flammability - FAA - Vertical Burn - 60 second	FAR 25.853 (a)(i)	Passes
Flammability - Vertical Burn - 12 second	FAR 25.853 (a)(ii)	Passes

**All values based on 0.125" unless otherwise stated*

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**