

Royalite® R906

Rigid ABS sheet

Product Description

Royalite® R906 thermoplastic sheet is an economical, rigid ABS product that provides an ideal balance of properties not available in most low-cost ABS sheets. It combines good impact strength and good formability with tensile strength, high stiffness.

Technical Properties

Property	Test Method	Value*
Specific Gravity (color dependent)	ASTM D-792	1.03 - 1.05
Izod Impact (Notched) 72°F	ASTM D-256	4.0 ft-lbs/in
Tensile Strength	ASTM D-638	4,250 psi
Flexural Strength	ASTM D-790	8,200 psi
Flexural Modulus	ASTM D-790	270,000 psi
Rockwell Hardness (R Scale)	ASTM D-785	92
Heat Deflection Temperature (@ 264 psi - annealed)	ASTM D-648	185°F
Coefficient of Linear Thermal Expansion	ASTM D-696	4.2 - 5.6 x10 ⁻⁵ in/in/°F
Mold Shrinkage	Internal	0.005 - 0.007 in/in
Motor Vehicle Safety Standard	FMVSS 302	Passes

*All values based on 0.125" unless otherwise stated

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**