

SurfaceChoice™ Realtree Xtra® Korad® over Floorlite C Flexible Sheet

Product Description

Floorlite C is an automotive-approved TPO sheet solution developed for use in a wide range of transportation applications. Spartech's specialty-formulated sheet incorporates 25 years of experience and expertise in the North American automotive flooring markets, and its unique physical characteristics provides customers a lightweight solution with superior toughness. The Realtree Xtra®Korad® overlay combines the Floorlite characteristics with the weather resistant features of Korad® film.

Technical Properties

Property	Test Method	Value
Specific Gravity	ASTM D-792	0.90
Hardness - Shore A	ASTM D-2240	94
Tensile Strength - Die A	ASTM D-412	MD 1,270 psi, AMD 1,100 psi
Ultimate Elongation - Die A	ASTM D-412	MD 940%, AMD 940%
Izod Impact (Notched) 73°F	ASTM D-256	n/a
Flexural Modulus	ASTM D-790	20,000 psi

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**