

TPR-2 Plus

Flexible Sheet

Product Description

TPR-2 Plus offers a flexible, low specific gravity product with a low gloss appearance. TPR-2 Plus is the material of choice for applications needing a slight decrease in flexibility but an increase in toughness from TPR-1.

Technical Properties

Property	Test Method	Value
Specific Gravity	ASTM D-792	0.94
Hardness - Shore A	ASTM D-2240	97
Tensile Strength - Die A	ASTM D-412	MD 1,450 psi
Ultimate Elongation - Die A	ASTM D-412	MD > 800%
Flammability	FMVSS 302	Pass
Gardner Gloss	ASTM D-523	<1.5 Gloss Units-60°
Taber Abrasion	ASTM D-1044	No wear through
Surface Resistivity	ASTM D-257	Insulative $10^{12.5}$ Ohm ²

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**